











Robust, space-saving bench scale, protected by stainless steel and IP65

Features

II Ideal for the food industry

Ideal for the robust industry

Stainless steel housing, rust-proof and easy to clean

Level indicator and foot screws to level the balance precisely, fitted as standard, to give the most accurate weighing results

Carrying grips on the underside of the scale for easy transportation

IP65: Protected against dust and water splashes

UNITS: Further weighing units see the internet

Technical data

Large LCD display, digit height 25 mm Dimensions of weighing plate (stainless steel) WxD 230x190 mm Overall dimensions WxDxH 230x300x130 mm Rechargeable battery pack internal, standard, operating time approx. 50 h, charging time approx. 12 h Net weight approx. 3,2 kg Permissible ambient temperature 0°C / 40°C



















Model	Weighing range [Max]	Readout [d]	Verification value [e]	Minimum load [Min]	Options	
					Verification MIII	DKD Calibr.
FFN 3K0.5IPN 🥃	3	0,5	-		-	963-127
FFN 6K1IPN	6	1	1	-	-	963-128
FFN 15K2IPN 📮	15	2	-	-	-	963-128
FFN 25K5IPN 🥃	25	5	-	-	-	963-128
Note: For application time, initial ver	s that require ve ification at a late			on at the same		
FFN 3K1IPM	3	1	1	20	965-227	963-127
FFN 6K2IPM	6	2	2	40	965-228	963-128
FFN 15K5IPM 🥃	15	5	5	100	965-228	963-128
FFN 25K10IPM	25	10	10	200	965-228	963-128